| ASSOCIATION CONNECTING ELECTRONICS INDUSTRIES® | terial Compo pyright 2005. IPC, Bannoc nternational and Pan-Ameri | tion with lower | level p | arts, the | declaration | n encom | | er level mate | erials for | which th | e item is an assembly ne manufacturer has eclaration. | | | | | | |
|--|---|------------------------|---------------------|---------------------|--------------------------|----------|------------------------|---------------|---|--|---|-----------|--------------|------------------|--|--|--|
| 1752-2 1.1 | IPC Web Site for Information on IPC-1752 Standard http://www.ipc.org/IPC-175x | | | | | | Form Type * Distribute | | | Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Materials and Mfg Informa | | | | | | | |
| Supplier Information | | | | | | | | | | | | | | | | | |
| Company Name * Company Unique | | | | Unique ID Au | Response Date * | | | F | Response Doci | ument ID | | | | | | | |
| SEMTECH CORPORATION | 00-847-9941 | | DUNS | 2013-11-19 | | | | | | | | | | | | | |
| Contact Name * | Title - Contact | | Phone - Con | Email - Contact * | | | | D " (| 0 1 1 | Λ (1 | | | | | | | |
| ROYA MOTAMEDI | | Quality Assurance C | ustomer S | 805-389-274 | rmotamedi@semtech.com | | | om | Duplicate | Contact - | -> Autho | orizea Re | presentative | | | | |
| Authorized Representative * | | Title - Representative | е | Phone - Rep | Email - Representative * | | | * 5 | Supplier Comments or URL for Additional Information | | | | | | | | |
| ROYA MOTAMEDI | | Quality Assurance C | ustomer S | 8 05-389-274 | 2 | rmota | medi@se | emtech.c | om | | | | | | | | |
| Requester Item Number | | Mfr Item Number | | Mfr Item Name | | Effectiv | e Date | Version Manu | | turing Site | Weight * | UC | OM | Unit Type | | | |
| | | SMDA24C.TBT | | 300 Watt Bidr | У | | | Phillipin | es | 75.875 | mg | | Each | | | | |
| Alternate Recommenda | dation | | | | | | | Alternate | Item Cor | nments | | | | • | | | |
| Manufacturing Proces | ss In | formation | | | | | | | | | | | | | | | |
| Terminal Plating / Grid Array Material | | | Terminal Base Alloy | | J-STD-020 MSL Ra | ating | ing Peak Proce | | Tempera | ature Max Time at Peak T | | perature | Number | of Reflow Cycles | | | |
| ` ' | | | CU Alloy | | 1 | | | 260 C | | | 30 se | econds | 3 | | | | |
| Comments SMDA24C.TBT is REAC | H-coi | mnliant product ne | r FU Regu | lation FC190 | 7/2006 to include | recen | t additio | n of SVH | C candi | date list of su | ihstances ii | n .lune | 2013 | | | | |

Save the fields in Import fields from a Clear all of the Lock the fields on this **Export Data** Import Data Reset Form Lock Supplier Fields this form to a file file into this form fields on this form form to prevent changes **RoHS Material Composition Declaration Declaration Type *** Detailed Rohs Directive Rohs Definition: Quantity limit of 0.1% by mass (1000 PPM) in homogeneous material for: Lead (Pb), Mercury, Hexavalent Chromium, Polybrominated Biphenvls (PBB). Polybrominated Diphenyl Ethers (PBDE) and quantity limit of 0.01% by mass (100 PPM) of homogeneous material for Cadmium 2002/95/EC Please indicate whether any homogeneous material (as defined by the RoHS Directive, EU 2002/95/EC and implemented by the laws of the European Union member states) of the part identified on this form contains lead, mercury, cadmium, hexavalent chromium, polybrominated biphenyls and/or polybrominated diphenyl ethers (each a ?RoHS restricted substance?) in excess of the applicable quantity limit identified above. If a homogeneous material within the part contains a RoHS restricted substance in excess of an applicable quantity limit, please indicate below which, if any, RoHS exemption you believe may apply. If the part is an assembly with lower level components, the declaration shall encompass all such components. Supplier certifies that it gathered the information it provides in this form using appropriate methods to ensure its accuracy and that such information is true and correct to the best of its knowledge and belief, as of the date that Supplier completes this form. Supplier acknowledges that Company will rely on this certification in determining the compliance of its products with European Union member state laws that implement the RoHS Directive. Company acknowledges that Supplier may have relied on information provided by others in completing this form, and that Supplier may not have independently verified such information. However, in situations where Supplier has not independently verified information provided by others, Supplier agrees that, at a minimum, its suppliers have provided certifications regarding their contributions to the part, and those certifications are at least as comprehensive as the certification in this paragraph. If the Company and the Supplier enter into a written agreement with respect to the identified part, the terms and conditions of that agreement, including any warranty rights and/or remedies provided as part of that agreement, will be the sole and exclusive source of the Supplier?s liability and the Company?s remedies for issues that arise regarding information the Supplier provides in this form. In the absence of such written agreement, the warranty rights and/or remedies of Supplier's Standard Terms and Conditions of Sale applicable to such part shall apply. 1 - Item(s) does not contain RoHS restricted substances per the definition above Supplier Acceptance * Accepted **RoHS Declaration *** Exemptions: If the declared item does not contain RoHS restricted substances per the definition above except for defined RoHS exemptions, then select the corresponding response in the RoHS Declaration above and choose all applicable exemptions. **Declaration Signature**

Instructions: Complete all of the required fields on all pages of this form. Select the "Accepted" on the Supplier Acceptance drop-down. This will display the signature area. Digitally sign the declaration (if required by the Requester) and click on Submit Form to have the form returned to the Requester.

Supplier Digital Signature

Homogeneous Material Composition Declaration for Electronic Products

Subltem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 sigma range of distribution unless otherwise noted).

Line Functions: +I Inserts a New Item /SubItem +M Inserts a new Material +C Inserts a new Substance Category +S Inserts a new Substance - Deletes the element line

| | Item/SubItem | | | Homogeneous | Weight | Unit of | | | Lovel | Substance Cotegory | | | Substance | CAS | Evennt | Weight | Unit of | Tolerance | | PPM |
|-------|---------------------|------|---|----------------|---------|---------|----|----|----------|--------------------|----|----|----------------------|-------------|--------|----------|---------|-----------|---|---------|
| | Name | | | Material | vveight | Measure | | | Level | Substance Category | | | Substance | CAS | Exempt | weight | Measure | - | + | PPIVI |
| +1 -1 | Die | +M - | M | Doped Silicon | 2.75 | mg | +C | -C | Supplier | | +S | -S | Si | 7440-21-3 | | 2.75 | mg | | | 36,243 |
| +1 -1 | Lead frame | +M - | M | C194 | 39.45 | mg | +C | -C | Supplier | | +S | -S | Cu | 7440-50-8 | | 38.4638 | mg | | | 506,93 |
| | - | | | | | | | | | | +S | -s | Fe | 7439-89-6 | | 0.92708 | mg | | | 12,218 |
| | | | | | | | | | | | +S | -s | Р | 7723-14-0 | | 0.011835 | mg | | | 155.98 |
| | | | | | | | | | | | +S | -s | Zn | 7440-66-6 | | 0.04734 | mg | | | 623.92 |
| +1 -1 | Die attach material | +M - | М | Conductive epo | 0.175 | mg | +C | -C | Supplier | | +S | -s | Epoxy resin | 129915-35-1 | | 0.01 | mg | | | 115.32 |
| | , | | | | | | | | | | +S | -s | Silver | 7440-22-4 | | 0.15 | mg | | | 1,960.4 |
| | | | | | | | | | | | +S | -s | Aromatic Amine | Proprietary | | 0.018 | mg | | | 230.64 |
| +1 -1 | Wire | +M - | М | Gold | 0.1 | mg | +C | -C | Supplier | | +S | -s | Au | 7440-57-5 | | 0.1 | mg | | | 1,317.8 |
| +1 -1 | Encapsulation | +M - | М | EME-G600 | 30 | mg | +C | -C | Supplier | | +S | -s | Fused Silica | 60676-86-0 | | 26 | mg | | | 345,96 |
| | , | | | | | | | | | | +S | -s | Epoxy Resin | 129915-35-1 | | 1.5 | mg | | | 19,769 |
| | | | | | | | | | | | +S | -s | Carbon black | 1333-86-4 | | 0.15 | mg | | | 1,976.9 |
| | | | | | | | | | | | +S | -s | Epoxy cresol novalac | 29690-82-2 | | 0.6 | mg | | | 7,907.7 |
| | | | | | | | | | | | +S | -s | Phenol resin | 9003-35-4 | | 1.5 | mg | | | 19,769 |
| +1 -1 | Lead finish | +M - | М | Alloy | 3.4 | mg | +C | -C | Supplier | | +S | -s | Tin | 7440-31-5 | | 3.4 | mg | | | 44,810 |